

Material Safety Data Sheet

Product Name: Snap Swab, K2-SPSB25, K2-SPSZ50, K2-SPSN1

General Use: Technical cleaning

Product Description: 91% Isopropyl Alcohol for technical cleaning. Squeeze or Snap the handle end and the swab will self saturate.

SECTION I

Distributor's Name & Address: Uline Shipping Supplies
12575 Uline Dr.
Pleasant Prairie, WI 53158
Ph: 262-612-4200

Complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200

SECTION II - Hazardous Ingredients/ Identity Information

Hazardous Components	CAS #	OSHA PEL.	ACGIH TLV	%
Isopropanol	67-63-0	400 ppm	400 ppm	91%

This Product contains the following chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372: NONE

SECTION III - Hazardous Identification

Appearance & Odor: Colorless, mobile liquid. Mild odor.

Health Hazards: Can cause severe lung damage and may be fatal if swallowed. Causes eye irritation. May be harmful if swallowed. May cause CNS depression.

Physical Hazards: FLAMMABLE. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Section IV - Emergency and First Aid Procedures:

EYE AND SKIN CONTACT: Flush with plenty of water.
Remove to fresh air; if breathing is difficult administer oxygen.
INHALATION: If conscious, drink large quantities of water. Do not induce vomiting.
INGESTION:

SECTION V - Fire and Explosion Hazard Data

Flash Point (Method Used): TCC 63°F
Flammable Limits: LEL 2.0 UEL 12.7
Extinguishing Media: Water, dry chemical CO2

Special Fire Fighting Procedures: Fire fighters should wear a NIOSH approved, pressure demand, self-contained breathing apparatus. Flammable vapors can be dispersed with water spray.

Unusual Fire and Explosion Hazards: Vapors are extremely flammable and can be ignited upon contact with a spark, flame, or a source of heat. Vapors are heavier than air and will travel along ground.

Work/Hygienic Practices: Do not eat, drink or smoke in work areas.

SECTION VI - Accidental Release Measures

FLAMMABLE. Vapors are flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Protective Measures:

Evacuate area of unprotected personnel. Eliminate potential sources of ignition (no smoking, flares, sparks or flames in immediate area). Stay upwind and keep out of low areas. Handling equipment must be bonded and grounded to prevent sparking. Wear appropriate personal protective equipment (refer to Section 8) when responding to spills.

Spill Management:

Shut off source of leak if safe to do so. Dike and contain spill. Use water spray (fog) to reduce vapors or divert vapor cloud drift. If vapor cloud forms, use water fog to suppress or blanket spill

area with foam. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Flush area with water to remove trace residue. Contain run-off from residue flush and dispose of properly. Prevent entry into waterways, sewer, basements or confined areas. For small spills: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

Disposal:

Proper disposal should be evaluated based on regulatory status of this material (refer to section 13), potential contamination from subsequent use and spillage, and regulations governing disposal in the local area.

Reporting:

Notify authorities if any exposures to the general public or environment occurs or is likely to occur.

SECTION VII – Handling and Storage

Do not taste or swallow. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Handling:

Surfaces that are sufficiently hot may ignite liquid material. Vapors are flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Do not store or handle in aluminum equipment at temperatures above 120° F (48.9° C).

Keep away from heat, sparks and flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors have dissipated. Use explosion-proof ventilation to prevent vapor accumulation while in use. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Air-dry contaminated clothing in a well-ventilated area before laundering. Static electricity may accumulate and create a fire hazard. Bond and ground handling equipment and transfer containers to prevent sparking.

Storage:

Keep containers closed when not in use.

Ground fixed equipment.

Container Warnings:

Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

SECTION VIII - Exposure Controls/Personal Protection

Material	Source	TWA	STEL
Isopropyl Alcohol	ACGIH –TLV	400 ppm (v)	500 ppm (v)
Isopropyl Alcohol	OSHA –PEL	400 ppm (v)	500 ppm (v)
Isopropyl Alcohol	OSHA -PEL-InterimStandard	400 ppm (v)	

Respiratory Protect (specify type): NIOSH approved self-contained breathing apparatus for concentrations above TLV limits (not necessary with normal use).

Ventilation: Local Exhaust: If needed to maintain workable concentration below permissible exposure limits.
Mechanical (general) See Above
Special:
Other:

Protective Gloves: Polyethylene, Neoprene or Polyvinyl alcohol

Eye Protection: Splash proof goggles

Other Protective Clothing or Equipment: Eye-wash fountain in immediate area. Personnel protective clothing and use of equipment must be in accordance with 29 CFR 1910.33 and 1910.134.

Work/Hygienic Practices: Do not eat, drink or smoke in work areas.

SECTION IX - Physical/Chemical Characteristics

Boiling Point:	180° F	Specific Gravity (water=1) 0.78
Vapor Pressure (mm Hg) @ 23.8°C	40	Melting Point N/A
Vapor Density (AIR=1)	2.07	Evaporation Rate (water =1) >1
Solubility in Water	Infinite	VOC-under 73 grams/liter
Appearance and Odor	Clear, colorless liquid, sharp alcohol odor	

Other Precautions: Avoid contact with strong oxidants. Do not use cutting torch on empty container. Do not smoke when using product. Intentional misuse by deliberately concentrating and inhaling vapor contents can be harmful or fatal.

SECTION X - Reactivity Data

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions to Avoid: N/A

Conditions to Avoid: NA

Incompatibility (Materials to avoid): Avoid strong oxidizing agents.

Hazardous Decomposition or Product: May form carbon dioxide and carbon monoxide, various hydrocarbons.

SECTION XI – Toxicological Information

Material Tested

Isopropyl Alcohol

Isopropyl Alcohol

Isopropyl Alcohol

Effects

Dermal - LD50

Inhalation - LC50

Oral - LD50

Test Results

12.87 g/kg (Rabbit)

19000 ppm (v) (Rat) 8 hour(s)

4.7 g/kg (Rat)

Eye Irritation:

Moderate irritation [Rabbit]

Skin Irritation:

Mild irritation [Rabbit]

Repeat Dose Testing:

In subchronic testing of IPA via the inhalation route, rats and mice exhibited reversible CNS effects, increases in mortality rate, increases in body weight, and effects of the liver and kidney. The organ effects were likely normal physiologic adaptive changes (liver) or unique rodent pathologic responses (kidney) to the high dose of IPA.

Reproductive and Developmental Toxicity:

IPA was not a primary reproductive or developmental toxicant in animal studies, but pregnant rabbits seemed more susceptible to IPA toxicity than non-pregnant animals.

Other Information:

Laboratory animals administered high doses of IPA in combination with known hepatotoxic chemicals exhibited enhanced liver toxicity.

SECTION XII – Environmental Fate and Effects:

This section will be updated as ecological reviews are completed

SECTION XIII – Disposal Considerations:

Product Disposal:

Under EPA RCRA (40 CFR 261) if this material becomes a waste material, it would be an ignitable hazardous waste, hazardous waste number D001. Refer to the latest EPA or state regulations regarding proper disposal.

SECTION XIV – Transportation Information:

US Department of Transportation Classification:

Proper Shipping Name: Isopropyl Alcohol
Identification Number: UN1219
Hazard Class/Division: 3 (Flammable Liquid)
Packing Group: II
Emergency Response Guide # 129

International Air Transportation Association Classification:

Dangerous Goods Regulations
Section 4
UN Number: 1219 Isopropyl Alcohol
Hazard Class/Division: 3 (Flammable Liquid)
Packing Group: II

For Air shipments domestic and international: All air shipments of this item from KICTeam are required to ship FedEx using FedEx labeling and packaging requirements. KICTeam has been certified by FedEx to ship this item by air for international and domestic shipments. We do not have certification from any other carrier.

SECTION XV – Regulatory Information:

The regulatory information provided is not intended to be comprehensive. Other federal, state and local regulations may apply to this material.

Federal Regulations:

Resource Conservation & Recovery Act (RCRA) Classification:
D001 (Ignitable Hazardous Waste).

Superfund Amendment & Reauthorization Act (SARA) Title III:

SARA Hazard Categories(311/312):

Fire Hazard. Immediate (Acute) Health Hazard.

SARA Toxic Release Inventory(TRI) (313):

Toxic Substances Control Act (TSCA) Inventory Status:

This material is listed on the EPA TSCA Inventory of Chemical Substances.

SECTION XVI – Other Information:

NFPA Rating (Health, Fire, Reactivity): 1, 3

Notice

We expressly disclaim all express or implied warranties to merchantability and fitness for a particular purpose with respect to the product or information provided recognized sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risk of their use, handling and disposal of the product, or from the publications or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.